



BUILDROCK FIX TILOGROUT-P

CEMENTITIOUS POLYMER MODIFIED TILE
GROUT

TECHNICAL SPECIFICATIONS & DATA SHEET

© EXCLUSIVE COPYRIGHTED CONTENT

DESCRIPTION

Buildrock Fix TilogROUT -P is a Single Component Polymer Modified Cementitious Tile Grout. It is used in Filling Tile Joint/ gaps. It holds the tiles together to provide a hard wearing, Non Dusting Surface to the floor tiles. It is applicable for both tile application Vertical as well as Horizontal Surface. It is available in different shade colors.

APPLICATION :

Buildrock fix TilogROUT - P Apply the Mixed Paste to the tile Joints with Squeeze trowel and remove the Paste with a damp Sponge. Do not exceed the working time of the grout. Allow 15 minutes for the grout to dry a little before cleaning off.

USES :

Buildrock fix TilogROUT - P is used to provide Smooth waterproof and wearing tile joint. It can be used in domestic interior floor as well as wall exterior tile and other some areas Hotels, Laboratories, bakeries, Supermarkets, restaurant, swimming pool etc.

ADVANTAGES :

- It is ready to use Powder only need Mixing water, and easy to clean,
- It is Highly waterproof Powder
- It is non dusting Powder
- Excellent Bond Strength
- Excellent abrasion strength.
- It is also UV resistant product no discoloration in dark Sunlight
- It is Available in different kinds of Shade Color.

METHODS OF APPLICATIONS:

SURFACE PREPARATION :

Ensure that before application of **Buildrock fix TilogROUT -P** that Joints should be free from laitance, Dust, oil and grease, dirt and other loose material. Surface prepared by Dry Paints Brush or washing with water, after that ensure Gaps/Joints are dry before Application of **Buildrock fix TilogROUT - P**.

MIXING :

Take a neat and clean Mixing Bowl or Container and charge 3 Parts of **Buildrock fix TilogROUT -P** and One part of Clean potable water and mix until lumps free smooth homogenous paste color is obtained. Don't Pour Extra Water as per the recommendation.

TECHNICAL SPECIFICATION :

PARAMETERS

Physical Appearance

Joint Width

Pot life

Movement Time

mixing Ratio(water : Grout)

Bond Strength

PROPERTIES

Free flowing powder with no agglomerates and free from hydrated Lumps

2-10 mm

30-35 min @27C

24 hrs

1:3

1.2 mpa

PACKING :

1kg Pouch and 10 kg Bag

SHELF LIFE :

12 Month from the date of Manufacturing in original packing, store in cool and dry place

HEALTH AND SAFETY :

Non Toxic Eco Friendly, avoid contact with Skin or Eyes.
If Contact with Skin: immediately wash with plenty of water

BUILDROCK ENGINEERING PVT. LTD.

REGISTERED OFFICE: PLOT NO.1, KHEWAT # 113, VILLAGE
FAKARPUR, PANCHGAON-JAMALPUR ROAD, GURUGRAM -
124 413, HARYANA, INDIA

PHONE: +91 124 3789989, +91 9811443000

WEBSITE: WWW.BUILDROCK.IN EMAIL: INFO@BUILDROCK.IN

DISCLAIMER : THE INFORMATION CONTAINED IN THIS TECHNICAL DATA SHEET IS GIVEN TO THE BEST OF OUR KNOWLEDGE AND THE RESULTS FROM EXTENSIVE TESTING IN ORDER TO REMAIN AS OBJECTIVE AS POSSIBLE. HOWEVER, IT CANNOT, IN ANY CASE BE CONSIDERED AS A WARRANTY INVOLVING OUR LIABILITY IN CASE OF MISUSE OR ANY DIFFERENT USE OF OUR PRODUCTS FROM THE "APPLICATION" PARAGRAPH OF THIS TECHNICAL DATA SHEET. SOME APPLICATION TESTS SHOULD BE CARRIED OUT BEFORE USING THE PRODUCT TO ENSURE THAT THE METHODS OF USE AND CONDITIONS OF APPLICATION OF THE PRODUCT ARE SATISFACTORY. OUR TECHNICAL ASSISTANCE IS AT THE DISPOSAL OF THE USERS.